



NIMA's Requirement: A Level 1 IKONOS Product

Frank Avila

NIMA/IPAN

AvilaF@nima.mil



Agenda

- Define NIMA's requirement.
- Show options available for new product.
- Show anomalies that exist with some options.
- Summary



Available Products

(to General Public)

- Carterra™ Geo
 - Carterra™ Reference
 - Carterra™ Map
 - Carterra™ Pro
 - Carterra™ Precision
 - Carterra™ Precision Plus
- Radiometric and Geometric Corrected
- Orthorectified





NIMA's Requirement

- NIMA required a product that would maintain radiometric fidelity for spectral applications.
- A product that would have minimal processing applied.
 - Less than Carterra™ Geo
- New Product : Radiometrically Corrected only (Level 1).




Variations of Level 1 Product

- Two processing parameters can be defined by the customer
 - Resampling method
 - Nearest neighbor, Bi-linear, or Bi-cubic
 - Modulation Transfer Function Compensation (MTFC)
 - On or Off



Resampling

- Process of interpolating the value of a transformed pixel.
 - NN - uses the value of the closes pixel
 - BL – uses values of four pixels in a 2x2 window
 - BC – uses the values of sixteen pixels in a 4x4 window



© 2000 Space Imaging, Inc. (All Rights Reserved)




MTFC

- MTFC is an edge sharpening technique used to partially restore image degradation.
 - MTFC OFF
 - MTFC ON



© 2000 Space Imaging, Inc. (All Rights Reserved)

UNCLASSIFIED



20 March 2001

Column Number
JACIE Conference
UNCLASSIFIED


© 2000 Space Imaging, Inc. (All Rights Reserved)



Existing anomalies

- Two anomalies exist with current Level 1 product.
 - Two lines of “data dropout”
Only occurs when MTFC is applied with NN resampling.

UNCLASSIFIED



Anomaly occurs when MTFC is applied with NN resampling.

20 March 2001

JACIE Conference
UNCLASSIFIED

10



Existing anomalies

- Two anomalies exist with current Level 1 product.
 - Two lines of “data dropout”
Only occurs when MTFC is applied with NN resampling.
 - “Color” pixels



Level 1 – NN/MTFC off



Level 1 – NN/MTFC on



Level 1 – CC/MTFC on



Level 2 – CC/MTFC on

© 2000 Space Imaging, Inc. (All Rights Reserved)



Existing anomalies

- Two anomalies exist with current Level 1 product.
 - Two lines of “data dropout”
Only occurs when MTFC is applied with NN resampling.
 - “Color” pixels
- SI expects to fix these anomalies with new array look-up tables that will be implemented soon.




Rectification, Resampling, and Adjustment

	Level 1	Level 2	Level 4
Product Type	Radiometric Corrected	Geometric Corrected	Orthorectified
Rectification	None	Ellipsoid	Terrain
Resampling	Synthetic Array	Map Projection	Map Projection
# of Resamplings	1	1	1
Block Adjustment	No	Yes	Yes



Statistical Comparison


Level 1NN vs. Level 2CC Product





Statistical Comparison

Level 1NN vs. Level 2NN Product





Summary

- A new product is available that preserves the radiometric fidelity.
- SI is working to fix the two anomalies outlined in the briefing.
- We need to evaluate other options that maintain radiometric fidelity while providing some geometric information.
- It is SI's position that MSI data should be processed with MTFC.



Product Accuracies*

Carterra Product	CE90 ⁽⁴⁾	RMS	NMAS ⁽¹⁾
Geo ⁽²⁾	50.0 m	23.3 m	1:100,000
Reference	25.4 m	11.8 m	1:50,000
Map	12.2 m	5.7 m	1:24,000
Pro	10.2 m	4.8 m	1:12,000
Precision	4.1 m	1.9 m	1:4,800
Precision Plus ⁽³⁾	2.0 m	0.9 m	1:2,400

Notes:

- Meets National Map Accuracy Standard for scale shown. Pixel size is 1 m.
- Geo products are not orthorectified; accuracy values do not include effect of terrain displacement.
- Precision plus does not have standard pricing.
- CE90 values are control, others are reference.

— Values acquired from Space Imaging website.

